

# NONAQUEOUS SECONDARY BATTERY AND PORTABLE DEVICE USING THE SAME

Publication number: JP2003187868

Publication date: 2003-07-04

Inventor: KITA FUSAJI; SAKATA HIDEO; KAMISORI HARUKI

Applicant: HITACHI MAXELL

Classification:

- international: **H01M4/02; H01M4/62; H01M10/40; H01M2/02; H01M6/10; H01M6/16; H01M10/42; H01M10/44; H01M4/02; H01M4/62; H01M10/36; H01M2/02; H01M6/04; H01M6/16; H01M10/42; (IPC1-7); H01M10/40; H01M4/02; H01M4/62**

- european: H01M10/40E5

Application number: JP20010389967 20011221

Priority number(s): JP20010389967 20011221

Also published as:



EP1458046 (A1)  
WO03054998 (A1)  
US2006183021 (A1)  
US2004072062 (A1)  
CN1500295 (A)

more >>


Report a data error here

## Abstract of JP2003187868

**PROBLEM TO BE SOLVED:** To provide a nonaqueous secondary battery that has excellent overcharge safety and can secure storage reliability because gas hardly occurs at high temperature storage.

**SOLUTION:** In the nonaqueous secondary battery, comprising a positive electrode, a negative electrode, and a nonaqueous electrolyte solution, the nonaqueous electrolyte solution contains a compound A in which a halogen group is bonded to a benzene ring, and an aromatic and/or heterocyclic compound B which is oxidized at a lower potential than that of this compound A, and the content of the compound A with respect to the whole nonaqueous electrolyte solution is not less than 1 mass% nor more than 15 mass% and the content of the compound B is not less than 0.005 mass% nor more than 3 mass%.

COPYRIGHT: (C)2003,JPO



Data supplied from the esp@cenet database - Worldwide